


# VULCAIN +



## MANUFACTURING & MACHINE TOOLS

Air and water



### APPLICATIONS

For pneumatic tooling or pneumatic control lines (e.g. paint spray guns).

### ADVANTAGES

- † Static conductive tube.
- † Very flexible hose especially at low temperatures.
- † Suitable for hot water.

### TECHNICAL DESCRIPTION

Inner tube: EPDM, black, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, blue, smooth.

Temperature range: -40°C to +100°C.

Electrical properties: conductive tube,  $R < 10^6 \Omega/m$ .



TRELLEBORG

VULCAIN +

$R < 10^6 \Omega/m$

Made in France





ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
6.0 ±0.4	3	12.0 ±0.5	20	80	25	0.11	20	0129662	
6.0 ±0.4	3	12.0 ±0.5	20	80	25	0.11	40	0129663	
6.0 ±0.4	3	12.0 ±0.5	20	80	25	0.11	120	0129665	
7.0 ±0.5	3.5	14.0 ±0.6	20	80	25	0.15	20	0129667	
7.0 ±0.5	3.5	14.0 ±0.6	20	80	25	0.15	40	0129668	3280
7.0 ±0.5	3.5	14.0 ±0.6	20	80	25	0.15	120	0129669	3240
8.0 ±0.5	3.5	15.0 ±0.6	20	60	30	0.16	20	0129670	
8.0 ±0.5	3.5	15.0 ±0.6	20	60	30	0.16	40	0129671	
8.0 ±0.5	3.5	15.0 ±0.6	20	60	30	0.16	120	0129672	
9.0 ±0.5	3.5	16.0 ±0.6	20	60	35	0.18	20	0129673	
9.0 ±0.5	3.5	16.0 ±0.6	20	60	35	0.18	40	0129675	
9.0 ±0.5	3.5	16.0 ±0.6	20	60	35	0.18	120	0129676	3240
10.0 ±0.5	4	18.0 ±0.6	20	60	40	0.23	20	0129678	
10.0 ±0.5	4	18.0 ±0.6	20	60	40	0.23	40	0129679	
10.0 ±0.5	4	18.0 ±0.6	20	60	40	0.23	120	0129680	
12.0 ±0.6	4	20.0 ±0.7	20	60	60	0.26	20	5501021	
12.0 ±0.6	4	20.0 ±0.7	20	60	60	0.26	40	5501020	
12.0 ±0.6	4	20.0 ±0.7	20	60	60	0.26	120	5501019	2400

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version





MANUFACTURING & MACHINE TOOLS

**Air and water**

For pneumatic tooling or pneumatic control lines (e.g. paint spray guns).

**Advantages**

- Static conductive tube.
- Very flexible hose especially at low temperatures.
- Suitable for hot water.

**Technical description**

**Inner tube:** EPDM, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** EPDM, blue, smooth.

**Temperature range:** -40°C to +100°C.

**Electrical properties:** conductive tube,  $R < 10^6 \Omega/m$ .

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (●) or min. order m
6.0 ±0.4	3.0	12.0 ±0.5	20	80	25	0.11	20	0129662	●
							40	0129663	●
							120	0129665	●
7.0 ±0.5	3.5	14.0 ±0.6	20	80	25	0.15	20	0129667	●
							40	0129668	3280
							120	0129669	3240
8.0 ±0.5	3.5	15.0 ±0.6	20	60	30	0.16	20	0129670	●
							40	0129671	●
							120	0129672	●
9.0 ±0.5	3.5	16.0 ±0.6	20	60	35	0.18	20	0129673	●
							40	0129675	●
							120	0129676	3240
10.0 ±0.5	4.0	18.0 ±0.6	20	60	40	0.23	20	0129678	●
							40	0129679	●
							120	0129680	●
12.0 ±0.6	4.0	20.0 ±0.7	20	60	60	0.26	20	5501021	●
							40	5501020	●
							120	5501019	2400

Tolerance on length: ±1% (ISO 1307 Standard).



Digital version

