

ASPIKLER N



**BUILDINGS &
CONSTRUCTION**

Drain and sewer cleaning



APPLICATIONS

For sewer suction.

Also for suction or delivery of abrasive materials on stationary systems and for cassette applications on sewer cleaning vehicles.

ADVANTAGES

- High resistance to abrasive environment and abrasive transportation media.
- Suitable both for suction and pressure.

TECHNICAL DESCRIPTION

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile cords with embedded steel helix.

Cover: SBR/NR, black, fabric impression.

Temperature range: -30°C to +80°C.





ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
100.0 ±1.0	8	116.5 ±1.5	6	15	0.9	450	4.3	20	0095016	ı
100.0 ±1.0	8	116.5 ±1.5	6	15	0.9	450	4.3	40	0096724	ı
102.0 ±1.0	8	118.0 ±1.5	6	15	0.9	450	4.38	20	5513565	ı
125.0 ±1.2	9.5	144.0 ±1.5	6	15	0.9	550	6.3	20	0094152	ı
125.0 ±1.2	9.5	144.0 ±1.5	6	15	0.9	550	6.3	40	5009671	ı
127.0 ±1.2	9.5	146.0 ±1.5	6	15	0.9	550	6.39	20	5513566	ı
150.0 ±1.2	10	170.0 ±1.5	6	15	0.9	650	7.77	20	5008847	ı
152.0 ±1.2	10	172.0 ±1.5	6	15	0.9	650	7.87	20	5513567	ı

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version





ASPIKLER N

BUILDINGS & CONSTRUCTION

Drain and sewer cleaning

For sewer suction.
Also for suction or delivery of abrasive materials on stationary systems and for cassette applications on sewer cleaning vehicles.

Advantages

- High resistance to abrasive environment and abrasive transportation media.
- Suitable both for suction and pressure.

Technical description

Inner tube: SBR, black, smooth.
Reinforcement: synthetic textile cords with embedded steel helix.
Cover: SBR/NR, black, fabric impression.
Temperature range: -30°C to +80°C.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (●) or min. order m
100.0 ±1.0	8.0	116.5 ±1.5	6	15	0.9	450	4.30	20	0095016	●
								40	0096724	200
102.0 ±1.0	8.0	118.0 ±1.5	6	15	0.9	450	4.38	20	5513565	●
125.0 ±1.2	9.5	144.0 ±1.5	6	15	0.9	550	6.30	20	0094152	●
								40	5009671	200
127.0 ±1.2	9.5	146.0 ±1.5	6	15	0.9	550	6.39	20	5513566	●
150.0 ±1.2	10.0	170.0 ±1.5	6	15	0.9	650	7.77	20	5008847	●
152.0 ±1.2	10.0	172.0 ±1.5	6	15	0.9	650	7.87	20	5513567	●

Tolerance on length: ±1% (ISO 1307 Standard).



Digital version

