

BIOCLEAN





Food industry High pressure cleaning

APPLICATIONS

High pressure cleaning specifically for food industries. Can also be used for transfer of any liquid foodstuffs.

ADVANTAGES

- Very flexible.
- Non-marking cover.
- Food grade quality white inner tube, oil resistant.
- Branding over red stripe for easy and quick identification.
- Contains no phthalate.

TECHNICAL DESCRIPTION

Inner tube: food grade quality oil resistant NBR, white, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant NBR/PVC, blue, smooth.

Temperature range: -20°C to +100°C.

STANDARD/APPROVAL

EU regulations No. 1935/2004, 2023/2006.	EU
FDA regulation No. 21 CFR 177.2600.	FDA
German legislation: BfR recommendation XXI cat. 3.	BfR
French legislation.	RF
All relevant migrations tests (France and FDA)	

All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.

COUPLINGS/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

100°C - Made in France

TRELLEBORG

PROC	ESSING EQUIPME	ENT	BIOCLEAN					
ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
7.9 ±0.5	15.9 ±0.6	60	180	50	0.2	20	5026076	I
7.9 ±0.5	15.9 ±0.6	60	180	50	0.2	40	5026077	I
7.9 ±0.5	15.9 ±0.6	60	180	50	0.2	120	5026109	I
9.5 ±0.5	18.0 ±0.7	60	180	60	0.25	20	5026110	I
9.5 ±0.5	18.0 ±0.7	60	180	60	0.25	40	5026113	I
9.5 ±0.5	18.0 ±0.7	60	180	60	0.25	80	5026114	I
9.5 ±0.5	18.0 ±0.7	60	180	60	0.25	120	5026115	I.
12.7 ±0.6	22.0 ±0.8	60	180	70	0.34	20	5012778	I.
12.7 ±0.6	22.0 ±0.8	60	180	70	0.34	30	5513514	¤
12.7 ±0.6	22.0 ±0.8	60	180	70	0.34	40	5012779	I
12.7 ±0.6	22.0 ±0.8	60	180	70	0.34	80	5026111	I.
12.7 ±0.6	22.0 ±0.8	60	180	70	0.34	120	5026112	I.
15.9 ±0.8	26.5 ±1.0	60	180	80	0.48	20	5026079	I
15.9 ±0.8	26.5 ±1.0	60	180	80	0.48	40	5026080	I
15.9 ±0.8	26.5 ±1.0	60	180	80	0.48	80	5026081	I
15.9 ±0.8	26.5 ±1.0	60	180	80	0.48	120	5026116	I
Tolerance on leng	Folerance on length: ±1% (ISO 1307 Standard).							

Digital version







PROCESSING EQUIPMENT

Food industry/High pressure cleaning

High pressure cleaning specifically for food industries. Can also be used for transfer of any liquid foodstuffs.

Advantages

- Very flexible.
- Non-marking cover.
- Food grade quality white inner tube, oil resistant. .
- Branding over red stripe for easy and quick identification.
- · Contains no phthalate.

Technical description Inner tube: food grade quality oil resistant NBR, white, smooth. Inner tube: tood grade quality oil resistant NBR, white, sn Reinforcement: synthetic textile. Cover: oil and weather resistant NBR/PVC, blue, smooth. Temperature range: -20°C to +100°C. Standard/Approval: EU regulations No. 1935/2004, 2023/2006. FDA regulation No. 21 CFR 177.2600. German legislation: BfR recommendation XXI cat. 3. French legislation. All relevant micrations tests (Erance and EDA) were perform All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.

Couplings/Fittings Specially designed fittings are available, please contact us for further information in order to get optimum connections.

ll m		O		Working pressure ^{bar}	Bursting pressure	Bending radius	Weight ^{kg/m}	Length ^m	Article number	Stock (●) or min. order m
7.9	±0.5	15.9	±0.6	60	180	50	0.20	20	5026076	•
								40	5026077	•
								120	5026109	•
9.5	±0.5	18.0	±0.7	60	180	60	0.25	20	5026110	•
								40	5026113	•
								80	5026114	•
								120	5026115	•
12.7	±0.6	22.0	±0.8	60	180	70	0.34	20	5012778	•
								30	5513514	¤
								40	5012779	•
								80	5026111	•
								120	5026112	•
15.9	±0.8	26.5	±1.0	60	180	80	0.48	20	5026079	•
								40	5026080	•
								80	5026081	•
								120	5026116	•
										¤ Upon availability.

Tolerance on length: ±1% (ISO 1307 Standard).



and embossed: week/year - batch number

