

# Claw Couplings

Swivelling, DIN 3489

- High-quality claw couplings, head made of malleable iron, thread connections and hose stem made of turned steel with special profile, zinc-plated and yellow passivated (free of chrome VI) with safety notches
- Easy 360° turning under pressure, therefore no hose twist
- Sealed by two O-rings, mounted on 2 teflon washers, safe and protected
- 100 % leakage-proof through machined seal holder, standard sealing can be used (GOER)
- Maximum bore for maximum flow rate
- On request with steam resistant sealing GDOR made of TFEP (surcharge: 6.72 euros)
- 100 % function check and sight control
- For flexible compressed air supply in construction and industry, if used as thread coupling assembled at the tool up to 10 times higher durability compared to rigid standard couplings! The swivel principle absorbs all vibrations!



## Materials

- Claw: Malleable iron zinc-plated and yellow passivated (free of chrome VI)
- Connector: Steel zinc-plated and yellow passivated (free of chrome VI)
- Seals: NBR

Max. Working Pressure	Temperature	Thread	Norm	Claw distance	Media	⊠
PN 16 bar	-40°C – +95°C	ISO 228	DIN 3489	42 mm	Air a.o.	5

## Claw Couplings with hose barb

Hose connection	L	B	L1	Passage	Weight	Type No.
Hose i.D. 13	87	63	41	10	221	SKG 13-DR
Hose i.D. 19	87	63	41	15	230	SKG 19-DR
Hose i.D. 25	87	63	41	19	260	SKG 25-DR

For hose clamps DIN 20039 A type SL (⊗ page 253) or crimping ferrules type LPH (⊗ page 401)

## Claw Couplings with hose barb and safety collar

Hose connection	L	B	L1	∅Collar	Passage	Weight	Type No.
Hose i.D. 13	96	63	41	24	10	236	SKB 13-DR
Hose i.D. 19	98	63	41	34	15	250	SKB 19-DR
Hose i.D. 25	98	63	41	39	19	290	SKB 25-DR

For hose clamps DIN 20039 B type SK (⊗ page 413)

## Claw Couplings with female thread

Thread connection	L	B	SW	L1	Passage	Weight	Type No.
G 1/2 f	61	63	24	15	17	240	KIG 12-DR
G 3/4 f	85	63	32	15	17	330	KIG 34-DR
G 1 f	90	63	41	15	17	430	KIG 10-DR

## Claw Couplings with male thread

Thread connection	L	B	SW	L1	Passage	Weight	Type No.
G 1/2 m	67	63	24	14	13	240	KAG 12-DR
G 3/4 m	68	63	24	15	17	236	KAG 34-DR
G 1 m	83	63	36	15	19	315	KAG 10-DR

## Original Rubber Rings

Resistance	L	D	D1	Material	Temp.°C	Media	Colour	Shore A	⊠	Weight	Type No.
Oil	11	34	20	NBR	-40 – +95	Compr. Air	black	65°	100	6	GOER
Steam	10	33	20	TFEP	-40 – +200	Steam	red	65°	10	6	GDOR

