



# EPDM rubber sheet

## Manticore Eco

<b>Quality:</b>	EPDM/SBR
<b>Colour:</b>	Black
<b>Temperature range:</b>	-30° to +90°C
<b>Specific gravity:</b>	1,45 grs/cm <sup>3</sup>
<b>Hardness:</b>	70 Shore A +/- 5
<b>Tensile strength:</b>	4 Mpa
<b>Elongation at break:</b>	200%

**Features:** Widely used weather and cold resistant industrial rubber quality with good mechanical properties and chemical resistance. Suitable for open air and good ozon resistance.

**Application:** Automotive industry, outdoor use and solar panels.

Thickness (mm)	Insertion(s) (no.)	Insertion type	Width (mtr)	Length (mtr)	Article nr.
1	0	-	1,4	20	EP7010 1/0
1,5	0	-	1,4	15	EP7010 1,5/0
2	0/1	nylon	1,2/1,4	10	EP7010 2/0
3	0/1/2	nylon	1,2/1,4	10	EP7010 3/0
4	0/1/2	nylon	1,2/1,4	10	EP7010 4/0
5	0/1/2	nylon	1,2/1,4	10	EP7010 5/0
6	0/2	nylon	1,2/1,4	10	EP7010 6/0
8	0/2	nylon	1,2/1,4	5	EP7010 8/0
10	0/2	nylon	1,2/1,4	5	EP7010 10/0
12	0	-	1,4	5	EP7010 12/0
15	0	-	1,4	5	EP7010 15/0
20	0	-	1,4	5/2	EP7010 20/0
25	0	-	1,4	5	EP7010 25/0
30	0	-	1,4	2	EP7010 30/0
40	0	-	1,4	2	EP7010 40/0
50	0	-	1,4	2	EP7010 50/0



**Rubber Europe**

Thickness Tolerances		
Over (mm)	Upto (mm)	Tolerance +/- (mm)
0.5	2	0.2
2	3	0.3
3	6	0.4
6	10	0.5
10	15	0.8
15	25	1.0

Roll length Tolerances	
Length (mm)	Tolerance +/- (mm)
1.000	50
5.000	250
10.000	500
20.000	1.000

Roll width Tolerances	
length (mm)	Tolerance +/- (mm)
900	18
1.000	20
1.220	24
1.300	26
1.400	28