

Rubber hose with galvanised steel spiral, for suction and transport of air and acid vapours.



 SMOOTH SURFACE ***

 FLEXIBILITY *****

 ABRASION RESISTANCE **

 TEMPERATURE RANGE -25 °c 125 °c

 CHEMICAL RESISTANCE TPV Table

 CRUSHING RESISTANCE ***

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23° m/H ₂ O	bending radius mm	wall thickness mm	Ø steel wire mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
25	1	26	30	3.5	25	0.7	0.8	8	left	120	30	On demand
30		31	35	3.5	30	0.7	0.8	8	left	140	30	On demand
32	1 1/4	33	37	3.5	32	0.7	0.8	8	left	145	30	On demand
35		36	40	3.5	35	0.7	0.8	8	left	160	30	On demand
38	1 1/2	39	44	3	38	0.7	1	10	left	180	30	On demand
40		41	46	3	40	0.7	1	10	left	200	30	In stock
45	1 3/4	46	51	3	45	0.7	1	10	left	230	30	In stock
50	2	51	56	2.5	50	0.7	1.2	12	left	280	30	In stock
60		61	66	2.5	60	0.7	1.2	12	left	320	30	In stock
63	2 1/2	64	69	2.5	63	0.7	1.2	12	left	340	30	In stock
65		66	71	2.5	65	0.7	1.2	12	left	360	30	On demand
70		71	77	2	70	0.7	1.4	14	left	420	30	In stock
75		76	82	2	75	0.7	1.4	14	left	440	30	In stock
80		81	87	1.7	80	0.7	1.4	14	left	480	30	In stock
85		86	92	1.7	85	0.7	1.4	14	left	500	30	On demand
90	3 1/2	91	97	1.7	90	0.7	1.4	14	left	520	30	In stock
100		101	107	1.4	100	0.7	1.6	16	left	660	30	In stock
110		111	117	1.4	110	0.7	1.6	16	left	720	30	In stock
120		121	127	1.2	120	0.7	1.6	16	left	780	30	In stock
125		126	132	1.2	125	0.7	1.6	16	left	800	30	In stock
130		131	137	1	130	0.7	1.6	16	left	840	30	In stock
140		141	147	1	140	0.7	1.6	16	left	900	30	In stock
150		151	157	0.7	150	0.7	1.8	18	left	1100	30	In stock
160		161	167	0.7	160	0.7	1.8	18	left	1160	30	In stock
170		171	177	0.5	170	0.7	1.8	18	left	1240	30	On demand
180		181	187	0.5	180	0.7	1.8	18	left	1300	30	In stock
200		201	207	0.4	200	0.7	1.8	18	left	1440	30	In stock
220		221	227	0.4	220	0.7	1.8	18	left	1600	15	In stock
250		252	259	0.3	250	0.8	2	22	left	1850	15	In stock
300		302	309	0.2	300	0.8	2	22	left	2300	15	In stock