


T ADAPERT UNF MALE ADJUSTABLE/DIN MALE/DIN MALE



ADATTATORE T MASCHIO DIN – MASCHIO UNF ORIENTABILE AL BRACCIO
 TÉ ORIENTABLE AVEC CONTRE ÈCROU UNF/DIN/DIN
 EINSTELLBARE L-VERSCHRAUBUNG MIT KONTERMUTTER –
 2 X DIN 24° / UNF-Z REDUZIERT
 RACOR ORIENTABLE EN T CON CONTROTUERCA UNF/DIN/DIN

F1 Metrisch, Metrico, Metric, Métrique, Métrico

F2 UNF

Code	Thread		Dimensions						Pressure		Series
	F1	F2	T1	H	L1	L2	L3	L4	Bar	Psi	
			mm	mm	mm	mm	mm	mm			
TME06LMOU04B.1	12X1,5	7/16"	6	14	9	14	20	21	315	4568	L
TME08LMOU04B.1	14X1,5	7/16"	8	14	9	16	20	23	315	4568	L
TME10LMOU06B.1	16X1,5	9/16"	10	14	10	17	24	24	315	4568	L
TME12LMOU06B.1	18X1,5	9/16"	12	19	10	19	26	26	315	4568	L
TME12LMOU08B.1	18X1,5	3/4"	12	19	11	19	26,5	26	315	4568	L
TME15LMOU08B.1	22X1,5	3/4"	15	22	11	21	30	28	315	4568	L
TME15LMOU10B.1	22X1,5	7/8"	15	22	12,7	21	30,3	28	315	4568	L
TME18LMOU10B.1	26X1,5	7/8"	18	27	12,7	24	34,3	26,5	315	4568	L
TME18LMOU12B.1	26X1,5	1.1/16"	18	27	15	24,5	35	28,5	315	4568	L
TME22LMOU12B.1	30X2	1.1/16"	22	27	15	28	37	28,5	160	2320	L
TME28LMOU16B.1	36X2	1.5/16"	28	33	15	31	42	31,5	160	2320	L
TME35LMOU20B.1	45X2	1.5/8"	35	41	15	38	48	35	160	2320	L
TME42LMOU24B.1	52X2	1.7/8"	42	48	15	38	49	39	160	2320	L
TME06SMOU04B.1	14X1,5	7/16"	6	14	9	15,5	23	38	400	5801	S
TME08SMOU06B.1	16X1,5	9/16"	8	14	10	18	27	45	400	5801	S
TME10SMOU06B.1	18X1,5	9/16"	10	19	10	18	27,5	45,5	400	5801	S
TME12SMOU08B.1	20X1,5	3/4"	12	19	11	22	33	23	400	5801	S
TME14SMOU10B.1	22X1,5	7/8"	14	22	12,7	22	31,3	26	400	5801	S
TME16SMOU10B.1	24X1,5	7/8"	16	27	12,7	25	37,3	26,5	400	5801	S
TME20SMOU12B.1	30X2	1.1/16"	20	27	15	28	38	32,5	400	5801	S
TME25SMOU16B.1	36X2	1.5/16"	25	33	15	30,5	42	34	400	5801	S
TME30SMOU20B.1	42X2	1.5/8"	30	41	15	36	54	38,5	250	3626	S
TME38SMOU24B.1	52X2	1.7/8"	38	48	15	34	54	44	250	3626	S