



CHEMISTAR SD /16 - EN 12115

FEP SUCTION AND DELIVERY HOSE FOR CHEMICAL PRODUCTS - EN 12115



APPLICATION

Suction and delivery hose for chemicals, petroleum and food stuffs as per EN 12115 specification. For deeper information, please check the chemical resistance table at the end of the catalog. The hose liner is FDA approved

TUBE

White, glossy, non conductive FEP (Fluorinated ethylen propylene)

REINFORCEMENT

High strength synthetic plies, with steel spirals and 2 crossing copper wires for hose grounding

COVER

Black, smooth, fire proof and antistatic ($R<10^6$ Ohm/m), cloth impression **CR** rubber compound, resistant to chemical products, ozone and weather

WORKING TEMPERATURE

-58°F +338°F -50°C +170°C

SPECIFICATIONS

EN 12115 / TRbF / FDA

		S.							A	a provide the second se	21 22 23
ID		0D		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
13	1/2	25	1	0.32	16	240	64	960	84	0.9	20
19	3/4	31	1 7/32	0.47	16	240	64	960	125	0.9	20
25	1	37	1 29/64	0.58	16	240	64	960	150	0.9	20
32	1 1/4	44	1 47/64	0.92	16	240	64	960	175	0.9	20
38	1 1/2	51	2	1.20	16	240	64	960	225	0.9	20
51	2	67	2 41/64	2.12	16	240	64	960	275	0.9	20

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

Tubi Gomma Torino S.p.a. 15040 Mirabello Monferrato (AL) - ITALY - Strada Statale 31 - km 39,4 Nr. 42 Ph: +39 0142.641300 Fax: +39 0142.641350 e-mail: com@tubigommatorino.it

Copyright © TUBI GOMMA TORINO S.p.a. - All rights reserved. The texts and images are owned by Tubi Gomma Torino S.p.A. Even partial reproduction of the catalog is prohibited. In the continuous search for technical and functional improvements, Tubi Gomma Torino S.p.A reserves the right to make changes to its products, which can be made without notice.