



# WATER MAX 130 °C\* - 100 bar

## PAINTED STEEL

**Ex** ATEX directive  
IIB 2 GD c T4 T135 °C X

- Supplied with:
- hoses in black synthetic rubber
  - zinc plated steel couplings
  - AISI 304 stainless steel swivel joint
  - "Viton®" seals



**FIXED**



**SWIVELLING**



	Article		Hose supplied	Connection	
	inlet	outlet		inlet	outlet
<b>S. 330</b>	8330.200	-	without hose	F1/2"G	F 3/8"-1/2"G
	8330.201	-	12m - 3/8" (995.313)	F1/2"G	M3/8"G
<b>S. 390</b>	8390.200	8380.200	without hose	F1/2"G	F3/8"-1/2"G
	8390.202	8380.202	17m - 3/8" (995.318)	F1/2"G	M3/8"G
<b>S. 430</b>	8430.200	8420.200	without hose	F1/2"G	F1/2"G
	8430.201	8420.201	10m - 1/2" (996.311)	F1/2"G	M1/2"G
	8430.202	8420.202	15m - 1/2" (996.316)	F1/2"G	M1/2"G
	for ABS hose reels Series 430 see page 152				
<b>S. 530</b>	8530.200	8520.200	without hose	F1/2"G	F1/2"G
	8530.201	8520.201	20m - 1/2" (996.321)	F1/2"G	M1/2"G
<b>S. 540</b>	8540.200	8550.200	without hose	F1"G	F1"G
	8540.202	8550.202	20m - 3/4" (997.320)	F1"G	M3/4"G
	8540.203 *	8550.203 *	15m - 1" (998.315)	F1"G	M1"G
<b>S. 560</b>	8560.200	-	without hose	F1"G	F1"G
	8560.205 *	-	30m - 1" (998.330)	F1"G	M1"G

\* 50 bar

\* 50 bar

\* Effective temperature only for versions without hose. For the maximum temperature of the versions with hose, contact technical dept.

### FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reels. The **template** supplied facilitates drilling of the holes and therefore hose reels fixing.

### SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reels installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.

