



AIR-WATER - 20 bar

PAINTED STEEL

Ex ATEX directive II 3 GD c X




Supplied with:
 - polyurethane hose
 - brass fitting
 - brass swivel joint
 - "Viton®" seals



	Article	Hose supplied	Connection	
			inlet	outlet
S. 288	8288.100	without hose	M3/8"G	F3/8"G
	8288.102	13m - 10x14,5 (972.113)	M3/8"G	M3/8"G
	8288.103	15m - 8x12 (971.115)	M3/8"G	M1/4"G
	8288.104	10m - 6x10 (971.010)	M3/8"G	M1/4"G
	8288.105	15m - 6x10 (971.015)	M3/8"G	M1/4"G
S. 328	8328.100	without hose	M3/8"G	F3/8"G
	8328.102	15m - 10x14,5 (972.115)	M3/8"G	M3/8"G
	8328.103	18m - 8x12 (971.118)	M3/8"G	M1/4"G
	8328.104	8m - 13x19 (976.108)	M1/2"G	M1/2"G
	8328.105	12m - 13x19 (976.112)	M1/2"G	M1/2"G
S. 378	8378.100	without hose	M3/8"G	F3/8"G
	8378.102	20m - 10x14,5 (972.120)	M3/8"G	M3/8"G
	8378.103	20m - 8x12 (971.120)	M3/8"G	M1/4"G
	8378.104	10m - 13x19 (976.110)	M1/2"G	M1/2"G
	8378.105	15m - 13x19 (976.114)	M1/2"G	M1/2"G
S. 438	8430.100	without hose	F1/2"G	F1/2"G
	8438.101	10m - 13x19 (976.111)	F1/2"G	M1/2"G
	8438.102	15m - 13x19 (976.115)	F1/2"G	M1/2"G

FIXED OVERALL DIMENSIONS



Art.	A	B	C	D	E	F	G	H	I	1-m ³	kg *
S. 288	186	140	196	226	110	310	300	320	-	0,037	from 7 to 12
S. 328	186	140	196	226	110	355	350	365	20	0,045	from 8 to 13
S. 378	186	140	196	226	110	400	390	410	20	0,068	from 10 to 17
S. 438	186	140	196	226	115	450	420	460	20	0,098	from 14 to 21

* The list shows min and max weight for each series: min weight refers to version without hose, max weight refers to heaviest version which depends on hose length and diameter.

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reels. The **template** supplied facilitates drilling of the holes and there fore hose reels fixing.

