



GREASE - 400 bar

PAINTED STEEL




ATEX directive
IIB 2 GD c T4 T135 °C X

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- carbon steel swivel joint
- "polyurethane" seals



FIXED



SWIVELLING



	Article	Article	Hose supplied	Connection	
				inlet	outlet
S. 330	8330.500 *	-	without hose	F3/8"G	F3/8"G
	8330.501	-	12m - 1/4" (993.511)	F3/8"G	M1/4"G
S. 390	8390.500 *	8380.500 *	without hose	F3/8"G	F3/8"G
	8390.501	8380.501	12m - 1/4" (993.511)	F3/8"G	M1/4"G
	8390.502	8380.502	16m - 1/4" (993.516)	F3/8"G	M1/4"G
S. 430	8430.500 *	8420.500 *	without hose	F3/8"G	F1/2"G
	8430.501	8420.501	12m - 1/4" (993.512)	F3/8"G	M1/4"G
	8430.502	8420.502	18m - 1/4" (993.518)	F3/8"G	M1/4"G
	8430.505	8420.505	10m - 3/8" (995.710)	F3/8"G	M1/4"G
	8430.506	8420.506	15m - 3/8" (995.715)	F3/8"G	M1/4"G
	for ABS hose reels Series 430 see page 152				
S. 530	8530.500 *	8520.500 *	without hose	F3/8"G	F1/2"G
	8530.501	8520.501	20m - 3/8" (995.720)	F3/8"G	M1/4"G
	8530.502	8520.502	25m - 3/8" (995.725)	F3/8"G	M1/4"G
S. 540	8540.500 *	8550.500 *	without hose	F3/8"G	F1/2"G
	8540.501	8550.501	30m - 3/8" (995.730)	F3/8"G	M1/4"G

* 600 bar

* 600 bar

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reels. The **template** supplied facilitates drilling of the holes and therefore hose reels fixing.

SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reels installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.

