



NBR rubber sheet

Satyr Eco

Quality:	NBR/SBR
Colour:	Black
Temperature range:	-30° to +90°C
Specific gravity:	1,45 grs/cm ³
Hardness:	70 Shore A +/- 5
Tensile strength:	4 Mpa
Elongation at break:	200%

Features: Widely used oil and grease resistant industrial rubber quality with good mechanical properties.

Application: Chemical industries, garages, workshops et cetera.

Thickness (mm)	Insertion(s) (no.)	Insertion type	Width (mtr)	Length (mtr)	Article nr.
1	0	-	1,4	20	NB7010 1/0
1,5	0/1	nylon	1,4	15	NB7010 1,5/0
2	0/1	nylon	1,2/1,4	10	NB7010 2/0
3	0/1/2	nylon	1,2/1,4	10	NB7010 3/0
4	0/1/2	nylon	1,2/1,4	10	NB7010 4/0
5	0/1/2	nylon	1,2/1,4	10	NB7010 5/0
6	0/2	nylon	1,2/1,4	10	NB7010 6/0
8	0/2	nylon	1,2/1,4	5	NB7010 8/0
10	0/2	nylon	1,2/1,4	5	NB7010 10/0
12	0	-	1,4	5	NB7010 12/0
15	0	-	1,4	5	NB7010 15/0
20	0	-	1,4	2/5	NB7010 20/0
30	0	-	1,4	2	NB7010 30/0
40	0	-	1,4	2	NB7010 40/0
50	0	-	1,4	2	NB7010 50/0



Rubber Europe

Thickness Tolerances		
Over (mm)	Upto (mm)	Tolerance +/- (mm)
0.5	2	0.2
2	3	0.3
3	6	0.4
6	10	0.5
10	15	0.8
15	25	1.0

Roll length Tolerances	
Length (mm)	Tolerance +/- (mm)
1.000	50
5.000	250
10.000	500
20.000	1.000

Roll width Tolerances	
length (mm)	Tolerance +/- (mm)
900	18
1.000	20
1.220	24
1.300	26
1.400	28