





FUEL AND MINERAL OIL DELIVERY HOSE FOR TANK REELS



APPLICATION

Delivery hose for mineral oils, diesel fuel and gasoline with aromatic contents up to 50%. Suitable for hose reels

TUBE

Black, smooth NBR, (80 Shore A) rubber compound

REINFORCEMENT

High strength synthetic plies and 1 copper wire for hose grounding

COVER

Black, smooth, antistatic (R<10 6 Ohm/m) cloth impression NBR rubber compound, resistant to oils, fuels and weather

WORKING TEMPERATURE

-22°F +176°F -30°C +80°C

-		S.			()				A	21 22 23
ID		0D		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
19	3/4	32	1 1/4	0.70	18	270	54	810	175	40
25	1	38	1 1/2	0.85	18	270	54	810	255	40/50/61
32	1 1/4	44	1 47/64	1.00	18	270	54	810	330	40/50/61
38	1 1/2	52	2 15/32	1.32	18	270	54	810	380	40/50/61
40	1 37/64	54	2 1/8	1.38	18	270	54	810	405	40/50/61
45	1 25/32	59	2 21/64	1.51	18	270	54	810	455	40/50/61
50	1 31/32	63	2 21/34	1.60	18	270	54	810	510	40/50/61
51	2	64	2 17/32	1.63	18	270	54	810	510	40/50/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

🕑 PETROSTAR D W.P. 18 BAR ITALY (I) tubi gomma torino	
---	--

Tubi Gomma Torino S.p.a. 15040 Mirabello Monferrato (AL) - ITALY - Strada Statale 31 - km 39,4 Nr. 42 Ph: +39 0142.641300 Fax: +39 0142.641350 e-mail: com@tubigommatorino.it

Copyright © TUBI GOMMA TORINO S.p.a. - All rights reserved. The texts and images are owned by Tubi Gomma Torino S.p.A. Even partial reproduction of the catalog is prohibited. In the continuous search for technical and functional improvements, Tubi Gomma Torino S.p.A reserves the right to make changes to its products, which can be made without notice.