


# Pneumatic Fittings


made of Brass Nickel-Plated



## Thread stem adapters with parallel male thread

Thread connection	Hose connection	L	SW	L1	L2	Weight	Type No.
G 1/8 m	Hose i.D. 6	32	13	7	20	10	VPG 260-186
G 1/8 m	Hose i.D. 9	32	13	7	20	13	VPG 260-189
G 1/4 m	Hose i.D. 6	34	17	9	20	16	VPG 260-146
G 1/4 m	Hose i.D. 9	34	17	9	20	19	VPG 260-149
G 3/8 m	Hose i.D. 9	35	19	10	20	24	VPG 260-389
G 3/8 m	Hose i.D. 14	39	19	10	24	29	VPG 260-3814
G 1/2 m	Hose i.D. 14	40	24	10	24	39	VPG 260-1214
G 3/4 m	Hose i.D. 20	47	30	12	28	87	VPG 260-3420


For hose clips type ZOS (© page 130), type HS (© page 131) or crimping ferrules type LPH (© page 133), Thread sealing with PVC sealing ring type HPD (© page 212)



## Thread stem adapters with parallel female thread

Thread connection	Hose connection	L	SW	L1	L2	Weight	Type No.
G 1/8 f	Hose i.D. 6	31	13	9	20	13	VPG 250-186
G 1/4 f	Hose i.D. 6	34	17	11	20	20	VPG 250-146
G 1/4 f	Hose i.D. 9	34	17	11	20	23	VPG 250-149
G 3/8 f	Hose i.D. 9	35	22	12	20	27	VPG 250-389
G 1/2 f	Hose i.D. 13	41.5	24	14	24	45	VPG 250-1213

For hose clips type ZOS (© page 130), type HS (© page 131) or crimping ferrules type LPH (© page 133)



## Hexagon Locking nut with parallel female thread

Thread connection	L	SW	L1	Weight	Type No.
G 1/8 f	12	14	9	11	VE 265-18
G 1/4 f	14	17	10	17	VE 265-14
G 3/8 f	15.5	22	11	27	VE 265-38
G 1/2 f	17	24	12	28	VE 265-12
G 3/4 f	17.5	30	13	47	VE 265-34



## Hexagon Locking nut with parallel male thread

Thread connection	L	SW	L1	Weight	Type No.
G 1/8 m	10.5	14	6	8	VE 261-18
G 1/4 m	13	17	8	14	VE 261-14
G 3/8 m	14	19	9	18	VE 261-38
G 1/2 m	15.5	24	10	27	VE 261-12
G 3/4 m	17.5	30	12	53	VE 261-34

Thread sealing ring with PVC washers type HPD (© page 212)