


Screwings and Components

Brass MS 58 plain


Female thread standard hose stems

Thread connect.	Hose con.	L	SW	L1	L2	Passage	⊠	Weight	Type No.
M 14x1.5 f	Hose i.D. 9	37.5	17	12	22.5	6	10	20	TI 14159 MHL
M 16x1.5 f	Hose i.D. 13	40	22	12	25	9	10	45	TI 161513 MHL
M 24x1.5 f	Hose i.D. 19	55	30	18	35	13	10	108	TI 241519 MHL



Male thread standard hose stems with inner cone DIN 3863 – 60° cone

Thread connect.	Hose con.	L	SW	L1	L2	Passage	⊠	Weight	Type No.
M 8x0.75 m	Hose i.D. 6	33.5	11	7	22.5	4.5	10	13	G 875-6 THL
M 8x0.75 m	Hose i.D. 9	33.5	11	7	22.5	4.5	10	19	G 875-9 THL
M 10x1 m	Hose i.D. 9	33.5	11	7	22.5	6	10	20	G 101-9 THL
G 1/8 m	Hose i.D. 9	33.5	11	7	22.5	6	10	20	G 18-9 THL
G 1/4 m	Hose i.D. 9	37.5	15	9	22.5	6	10	21	G 14-9 THL
G 1/4 m	Hose i.D. 13	40	15	9	25	8	10	34	G 14-13 THL
M 12x1.5 m	Hose i.D. 13	40	15	9	25	7	10	35	G 1215-13 THL
M 14x1.5 m	Hose i.D. 13	40	15	9	25	9	10	36	G 1415-13 THL
G 3/8 m	Hose i.D. 9	37.5	17	9	22.5	6	10	27	G 38-9 THL
G 3/8 m	Hose i.D. 13	40	17	9	25	9	10	36	G 38-13 THL
M 16x1.5 m	Hose i.D. 13	40	17	9	25	9	10	36	G 1615-13 THL
G 1/2 m	Hose i.D. 19	50	22	12	35	13	10	73	G 12-19 THL
M 24x1.5 m	Hose i.D. 19	56	27	16	35	13	10	114	G 2415-19 THL
G 3/4 m	Hose i.D. 19	56	27	16	35	13	10	125	G 34-19 THL



Male thread standard hose stems 90° (metric threads DIN 158/ R-thread DIN EN 10226)

Thread connect.	Hose con.	L	SW	L1	L2	Passage	⊠	Weight	Type No.
M 5x0.5 m	Hose i.D. 5	15.5	9	5	18	2.7	10	9	ESHMC505-5SL-90
M 8x0.75 m	Hose i.D. 5	17.5	9	5	20	2.7	10	11	ESHMC875-5SL-90
M 8x0.75 m	Hose i.D. 9	27	15	9	20	4.5	10	35	ESHM 875-9SL-90
M 10x1 m	Hose i.D. 9	27	15	9	20	6	10	38	ESHM 101-9SL-90
R 1/8 m	Hose i.D. 9	27	15	9	20	6	10	38	ESHM 18-9SL-90*
M 14x1.5 m	Hose i.D. 13	34	17	11	24	9	10	47	ESH 1415-13SL90
R 1/4 m	Hose i.D. 13	34	17	11	24	9	10	48	ESH 14-13SL-90*
R 1/2 m	Hose i.D. 19	47	24	16	32	13	10	158	ESHG 12-19SL-90*
M 24x1.5 m	Hose i.D. 19	47	24	16	32	13	10	165	ESHG2415-19SL90

Suitable hose clips, double-ear clips or crimping ferrules for standard hoses (© Page 194 - 197)



Male thread quick-fit hose stems for quick-fit hoses – 60° cone

Thread connect.	Hose con.	L	SW	L1	L2	Passage	⊠	Weight	Type No.
M 10x1 m	Hose i.D. 6	41	11	9	28	6	10	20	G 101-6 TH
G 1/8 m	Hose i.D. 6	39	14	7	28	4	10	16	G 18-6 TH
G 1/4 m	Hose i.D. 6	39	17	7	28	4	10	19	G 14-6 TH
G 1/8 m	Hose i.D. 10	39	14	7	28	5	10	21	G 18-10 TH
G 1/4 m	Hose i.D. 10	39	17	7	28	7	10	23	G 14-10 TH
G 1/4 m	Hose i.D. 13	39	17	7	28	9	10	28	G 14-13 TH
M 14x1.5 m	Hose i.D. 10	42	15	9	28	7	10	26	G 1415-10 TH
G 3/8 m	Hose i.D. 10	43	17	10	28	7	10	32	G 38-10 TH
G 3/8 m	Hose i.D. 13	43	17	10	28	9	10	36	G 38-13 TH
G 1/2 m	Hose i.D. 10	43	22	10	28	7	10	41	G 12-10 TH
G 1/2 m	Hose i.D. 13	43	22	10	28	9	10	41.5	G 12-13 TH
G 1/2 m	Hose i.D. 16	58	22	12	38	13	10	70	G 12-16 TH
G 3/4 m	Hose i.D. 16	62	27	16	38	13	10	120	G 34-16 TH
G 3/4 m	Hose i.D. 19	62	27	16	38	14	10	135	G 34-19 TH



Quick-fit hose menders with/without safety collar for quick-fit hoses

Hose connection	L	L1	Passage	Version	⊠	Weight	Type No.
Hose i.D. 13	58	28	10	w safety collar	10	24	SV 13 R-TH
Hose i.D. 13	47	22.5	10	w/o safety collar	10	26	SV 13 R-THO
Hose i.D. 16	47	22.5	10	w/o safety collar	10	39	SV 16 R-THO

Safety instruction: Only use quick-fit hose stems in combination with suitable quick-fit hoses!

Coloured marking rings (© Page 189)

*Hose stems with inch threads are nickel-plated for simple distinction

