



## Mining & Para Centaur Black (BL)

|                             |                          |
|-----------------------------|--------------------------|
| <b>Quality:</b>             | NR (Para)                |
| <b>Colour:</b>              | Black                    |
| <b>Temperature range:</b>   | -30° to +70°C            |
| <b>Specific gravity:</b>    | 1,17 grs/cm <sup>3</sup> |
| <b>Hardness:</b>            | 60 Shore A +/- 5         |
| <b>Tensile strength:</b>    | 13 Mpa                   |
| <b>Elongation at break:</b> | 450%                     |
| <b>Abrasion:</b>            | 120 mm <sup>3</sup>      |

**Features:** Good resistance to abrasion with high tensile strength, elasticity and excellent adhesion. (Also available with bonding layer).

**Application:** Widely used in rubber lining for material handling equipment or any other crucial application to reduce wear and tear.

| Thickness (mm) | Width (mtr) | Length (mtr) | Also available with | With bonding layer available with | Article nr.  |
|----------------|-------------|--------------|---------------------|-----------------------------------|--------------|
| 3              | 1,4         | 10           |                     |                                   | AB60117 3/0  |
| 4              | 1,4         | 10           | -                   |                                   | AB60117 4/0  |
| 5              | 1,4         | 10           | -                   |                                   | AB60117 5/0  |
| 6              | 1,4/2       | 10           | bonding layer       | 1,4/2                             | AB60117 6/0  |
| 8              | 1,4/2       | 10           | bonding layer       | 1,4/2                             | AB60117 8/0  |
| 10             | 1,4/2       | 10           | bonding layer       | 1,4/2                             | AB60117 10/0 |
| 12             | 2           | 10           | bonding layer       | 2                                 | AB60117 12/0 |
| 15             | 1,4/2       | 10           | bonding layer       | 2                                 | AB60117 15/0 |
| 20             | 1,4/2       | 10           | bonding layer       | 1,4/2                             | AB60117 20/0 |
| 25             | 1,4/2       | 10           | bonding layer       | 2                                 | AB60117 25/0 |
| 30             | 1,4/2       | 10           | bonding layer       | 2                                 | AB60117 30/0 |