


# WaterProfi Quick Connect Couplings

## Series WS made of Brass Nickel-Plated

**DN 9**



Also in  
Stainless Steel  
Series WSE  
page 349

**WaterProfi**  
LOWEST PRICE

- High quality one-hand operation quick connect couplings made of brass MS 58 nickel-plated
- Easy to connect, high pressure spectrum, superior sealing characteristics and durable, robust, safe and reliable
- Ergonomic sleeve design for perfect handling and compact size
- High water flow due to optimized passage
- Spray nozzle with water flow shut off and flow control from mist to full jet
- Interchangeable with standard plug profile types, available with shut-off valves or straight-through
- **Universal one-hand operation Quick Connect Coupling for water lines in industry, trades, agriculture, land scaping, gardening or household**

### Materials

- Body, sleeve, pin holder, valve, plug: Brass MS 58 nickel-plated
- Pins: Stainless steel 1.4305
- Springs: Spring steel 1.4310
- O-rings: EPDM
- Claw: Brass MS 58 plain
- Spray Nozzle: Aluminium/ Brass MS 58 nickel-plated

Max. Working Pressure	Temperature	DN	Thread	Operation	Type of valve	Media	CE
PN 16 bar	+95°C	9	ISO 228	One-hand	single/straight through	Water	5

### WaterProfi Couplings with hose connection

Hose connection	L	D	L1	Weight	Type No.w/o valve	Type No.w valve
Hose I.D. 13	75	32	30	165	WS 13 T	WS 13 TAB
Hose I.D. 16	75	32	30	166	WS 16 T	WS 16 TAB
Hose I.D. 19	75	32	30	173	WS 19 T	WS 19 TAB
Hose I.D. 25	75	32	30	185	WS 25 T	WS 25 TAB

### WaterProfi Couplings with female thread

Thread connection	L	SW	D	L1	Weight	Type No.o.Ventil	Type No.w valve
G 1/2 f	56	27	32	11	170	WS 12 I	WS 12 IAB
G 3/4 f	56	30	32	11	172	WS 34 I	WS 34 IAB

### WaterProfi Couplings with male thread

Thread connection	L	SW	D	L1	Weight	Type No.o.Ventil	Type No.w valve
G 1/2 m	61	27	32	10	178	WS 12 A	WS 12 AAB
G 3/4 m	62	30	32	10	198	WS 34 A	WS 34 AAB

### WaterProfi Couplings with squeeze nut

Hose connection	L	D	L1	Weight	Type No.w/o valve	Type No.w valve
Hose 13x3	59	32	21	175	WS 13 TQ	WS 13 TQAB
Hose 19x4	64	32	28	235	WS 19 TQ	WS 19 TQAB

### WaterProfi Screwing hose stems (for combination with WaterProfi couplings with female thread)

Thread connection	Hose con.	L	L1	L2	Passage	Weight	Type No.
G 3/4 m	Hose I.D. 13	41	32	9	10	37	WS 13 GT
G 3/4 m	Hose I.D. 16	41	32	9	13	38	WS 16 GT
G 3/4 m	Hose I.D. 19	41	32	9	15	49	WS 19 GT
G 3/4 m	Hose I.D. 25	41	32	9	19	68	WS 25 GT

### System Adapter WaterProfi Claw Coupling - Quick Connect Coupling DN 9

Connection	L	B	Weight	Type No.
WaterProfi Claw Coupling - Coupling WS DN 9	76.5	54.2	254	WSK-WPA
WaterProfi Claw Coupling - Plug WS DN 9	59.5	54.2	160	WSS-WPA



# WaterProfi Quick Connect Couplings


made of Brass Nickel-Plated, **Series WS**

**DN 9**

## WaterProfi Plugs with hose connection

Hose connection	L	D	L1	L2	Weight	Type No.
Hose I.D. 13	58	24	32	24	53	WS 13 S
Hose I.D. 16	58	24	32	24	53	WS 16 S
Hose I.D. 19	58	24	32	24	62	WS 19 S
Hose I.D. 25	58	27	32	24	88	WS 25 S

**WaterProfi** by LOECKE



## WaterProfi Plugs with female thread (with female thread sealing ring)

Thread connection	L	SW	L1	L2	Weight	Type No.
G 1/2 f	38	27	10	24	70	WS 12 NI
G 3/4 f	38	30	10	24	68	WS 34 NI
G 1 f	38	36	10	24	77	WS 10 NI



## WaterProfi Plugs with male thread

Thread connection	L	SW	L1	L2	Weight	Type No.
G 1/2 m	40	24	10	24	55	WS 12 NA
G 3/4 m	41	30	10.5	24	76	WS 34 NA



## WaterProfi Plugs with squeeze nut

Hose connection	L	SW	L1	L2	Weight	Type No.
Hose 13x3	53	19	16	24	106	WS 12 SQ
Hose 19x4	58	19	21	24	154	WS 19 SQ



## WaterProfi System Adapter

Connection	L	D	L1	L2	Weight	Type No.
DN 9 - DN 9	52	24	24	24	70	WSA



## WaterProfi Spray Nozzle with plug-/hose connection-/male thread

Connection	L	B	L1	Passage	∅	Weight	Type No.
Plug WaterProfi	118	33	24	6.5	1	308	WSD-S
Hose I.D. 13	126	33	32	6.5	1	302	WSD 13 T
Hose I.D. 16	126	33	32	6.5	1	303	WSD 16 T
Hose I.D. 19	126	33	32	6.5	1	312	WSD 19 T
Hose I.D. 25	126	33	32	6.5	1	328	WSD 25 T
G 1/2 m	106	33	12	6.5	1	297	WSD 12 A

