


# Safety Self-Venting Couplings

## Series ESIS with Sleeve Concept - single shut-off

According to  
ISO 4414/  
DIN EN 983/ BIA

### DN 7.8

Plug Profile (original size)



- Top-quality, ergonomic and very robust one-hand quick connect couplings made of brass MS 58 nickel-plated with hardened steel sleeve and perfect sealing as well as compact dimensions
- Very easy to connect, disconnection in two steps by pushing and pulling the sleeve in direction of arrow. Self-venting after step 1, safe decoupling after step 2
- Safe protection against whiplash-effect at best usability
- For safe handling of flexible compressed air lines
- High flow rates with low pressure drop due to patented OptiFlow by **LUDECKE**® valve technology
- **Attention: Safe operation can only be guaranteed when using hardened steel plugs**

#### Materials

- Body, valve body: Brass MS 58 nickel-plated
- Valve: Brass MS 58 plain
- Sleeve, plug: Hardened steel nickel-plated
- Seals: NBR (other materials on request)
- Springs: Stainless steel 1.4310
- Balls: Stainless steel 1.4034

Max. Working Pressure	Temperature	DN	Thread	Flow Rate	Operation	Type of valve	Media	Area	
PN 12 bar	-20°C – +100°C	7.8	ISO 228/DIN EN 10226	1800 l/min	One-hand	Single Shut-off	Compr. air	Europe	Coupl.5/ Plug10

#### Couplings with tapered male thread (thread coated)

Thread connection	L	SW	D	L1	Weight	Type No.
R 1/4 m	61	19	28	11	138	ESIS 14 A
R 3/8 m	62	19	28	12	147	ESIS 38 A
R 1/2 m	64	22	28	15	144	ESIS 12 A

#### Couplings with parallel female thread

Thread connection	L	SW	D	L1	Weight	Type No.
G 1/4 f	57	19	28	10	146	ESIS 14 I
G 3/8 f	57	19	28	10	144	ESIS 38 I
G 1/2 f	59	24	28	12	160	ESIS 12 I

#### Couplings with hose barb

Hose connection	L	SW	D	L1	Weight	Type No.
Hose i.D. 6	74	19	28	25	136	ESIS 6 T
Hose i.D. 8	74	19	28	25	136	ESIS 8 T
Hose i.D. 9	74	19	28	25	138	ESIS 9 T
Hose i.D. 10	74	19	28	25	138	ESIS 10 T
Hose i.D. 13	74	19	28	25	141	ESIS 13 T

For hose clips type ZOS (☺ page 130), type HS (☺ page 131) or crimping ferrules type LPH (☺ page 133)

#### Plugs with tapered male thread (thread coated)

Thread connection	L	SW	L1	L2	Weight	Type No.
R 1/8 m	33	13	9	20	14	ESI 18 NARS
R 1/4 m	35	14	11	20	18	ESI 14 NARS
R 3/8 m	36	17	12	20	23	ESI 38 NARS
R 1/2 m	40	22	15	20	47	ESI 12 NARS

#### Plugs with parallel female thread

Thread connection	L	SW	L1	L2	Weight	Type No.
G 1/8 f	32	13	9	20	16	ESI 18 NIS
G 1/4 f	33	17	10	20	24	ESI 14 NIS
G 3/8 f	33	19	10	20	25	ESI 38 NIS
G 1/2 f	35	24	12	20	40	ESI 12 NIS

#### Plugs with hose barb

Hose connection	L	D	L1	L2	Weight	Type No.
Hose i.D. 6	44	12	24	20	13	ESI 6 SS
Hose i.D. 8	44	12	24	20	18	ESI 8 SS
Hose i.D. 9	44	12	24	20	16	ESI 9 SS
Hose i.D. 10	44	12	24	20	18	ESI 10 SS
Hose i.D. 13	44	15	23	20	26	ESI 13 SS

For hose clips type ZOS (☺ page 130), type HS (☺ page 131) or crimping ferrules type LPH (☺ page 133)



**OptiFlow**  
by **LUDECKE**

