

# TEKNOJET 1SN 250

EN 1829-2

RECOMMENDED FOR:  
PROFESSIONAL WATER JET CLEANERS

RACCOMANDATO PER:  
MACCHINE IDROPULTRICI PROFESSIONALI

## Features:



## Alternative versions:



other colors available: BLUE, RED, GREY  
altri colori disponibili: BLU, ROSSO, GRIGIO

Code	Hose size			Outside diameter		Max working pressure		Min burst pressure		Min bend radius		Weight	
	D.N.	Inch	mm	Inch	mm	PSI	Bar	PSI	Bar	Inch	mm	Lb/ft	kg/mt
TJ1SN04	6	1/4"	6,4	0,52	13,1	3625	250	14500	1000	3,94	100	0,15	0,22
TJ1SN05	8	5/16"	7,9	0,58	14,7	3625	250	14500	1000	4,53	115	0,18	0,27
TJ1SN06	10	3/8"	9,5	0,67	17,0	3625	250	14500	1000	5,12	130	0,22	0,32
TJ1SN08	12	1/2"	12,8	0,79	20,1	3625	250	14500	1000	7,09	180	0,28	0,41


**TeknoJET 1SN 3/8"**

(9,5mm)

EN 1829-2

 -10°C / +150°C  
14°F / +302°F

 250 Bar  
25 MPa

**3625 Psi**

MARKING/MARCATURA: TRANSFER TAPE

**OPERATING****TEMPERATURE RANGE:**

- 10°C/+135°C  
(14°F to +275°F)  
with peak of +150°C (302°F)

**TEMPERATURA****DI ESERCIZIO:**

- 10°C/+135°C  
(14°F / +275°F)  
con punte di +150°C (302°F)

**TUBE:**

hot water, detergent and oil synthetic rubber

**SOTTOSTRATO:**

gomma sintetica resistente a acqua calda, detersivi e oli

**REINFORCEMENT:**

1 high tensile steel braid

**RINFORZO:**


1 treccia di acciaio ad alto carico

**COVER:**

synthetic rubber with extreme abrasion resistance

**COPERTURA:**

gomma sintetica con estrema resistenza all'abrasione

Note: TO ORDER BLU VERSION PLEASE ADD "B" TO THE CODE  
TO ORDER RED VERSION PLEASE ADD "R" TO THE CODE  
TO ORDER GREY VERSION PLEASE ADD "G" TO THE CODE  
TO ORDER FOREVER VERSION  PLEASE ADD "FV" TO THE CODE