



Rubber matting

Cobra

Quality:	NR/SBR
Colour:	Black
Temperature range:	-30° to +70°C
Specific gravity:	1,5 grs/cm ³
Hardness:	70 Shore A +/- 5
Tensile strength:	3 Mpa
Elongation at break:	200%

Features: Excellent anti-slip floor mat available in 2 meter width.

Application: Car trunks, horse trailers, entrances et cetera.

Thickness (mm)	Insertion(s) (no.)	Insertion type	Width (mtr)	Length (mtr)	Article nr.
3	0	-	1,7/1,8/2	10	SX70150C 3/0
4	2	nylon	2	10	SX70150C 4/2
5	0	-	2	10	SX70150C 5/0
6	2	nylon	1,7/2	10/12	SX70150C 6/2
8	1	nylon	1,7/2	10/12	SX70150C 8/1



Rubber matting

Feniks Insulation Mat

Quality:	EPDM/SBR
Temperature range:	-25° to +120°C
Specific gravity:	1,5 grs/cm ³
Hardness:	70 Shore A +/- 5
Tensile strength:	5 Mpa
Elongation at break:	250%
Abrasion:	300 mm ³

Features: Strong and abrasion resistant. Fine ribbed design on one side and a fine cloth impression pattern on the other side. Electrically insulating according to the standard IEC CEI 61111.

Application: Switchboard flooring to prevent against electrical shocks.

Class	Colour	Thickness (mm)	Proof Test Voltage	Resistance	Maximum use voltage	Width (mtr)	Length (mtr)	Article Nr.
2	Grey, Black	3	20 kV	30 kV	17 kV	1/1,2	10	ELS30000 3/0
4	Grey	4,5	40 kV	50 kV	36 kV	1/1,2	10	ELS50000 4,5/0