





BEER SUCTION AND DELIVERY HOSE



APPLICATION

Suction and delivery hose for beer, wine, alcohol (up to 96°), soft drinks

TUBE

White, smooth BIIR (butyl) rubber compound, food quality odourless and taste free

REINFORCEMENT

High strength synthetic plies with steel wire spirals

COVER

Orange, smooth, cloth impression EPDM rubber, resistant to abrasion, ozone and weather

WORKING TEMPERATURE

-40°F +248°F sterilization at 230°F for 30 minutes -40 °C +120 °C sterilizzazione a 110 °C massimo 30'

SPECIFICATIONS

FDA title 21 art.177.2600 (e) for liquid foods, BfR, ADI free, PHTHALATE free, CE 1935/2004

~		R			()				A		21 22 23
ID mm inch		0D mm inch		WEIGHT	WP bar psi		BP		BENDING RADIUS	VACUUM bar	COIL LENGTH
 19	3/4	 32	1 1/4	kg/m 0.78	10	150	bar 30	450	mm 80	0.9	40
25	1	38	1 1/2	0.92	10	150	30	450	115	0.9	40
32	1 1/4	45	1 25/32	1.19	10	150	30	450	145	0.9	40
38	1 1/2	50	1 31/32	1.48	10	150	30	450	180	0.9	40
51	2	64	2 17/32	1.87	10	150	30	450	245	0.9	40
63.5	2 1/2	80	3 5/32	2.68	10	150	30	450	340	0.9	40
65	2 9/16	82	3 15/64	2.85	10	150	30	450	350	0.9	40
76	3	92	3 5/8	3.23	10	150	30	450	410	0.9	40
102	4	120	4 23/32	4.70	10	150	30	450	580	0.9	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

I AGRABREW

W.P. 10 BAR (150 PSI) FDA BIR ADI mez PHTHALATE mez V ITALY (I) LUDI GOMMA LOTINO

Tubi Gomma Torino S.p.a. 15040 Mirabello Monferrato (AL) - ITALY - Strada Statale 31 - km 39,4 Nr. 42 Ph: +39 0142.641300 Fax: +39 0142.641350 e-mail: com@tubigommatorino.it