


## DIN MALE 45° ELBOW - BSPP MALE ADJUSTABLE



ADATTATORE 45° MASCHIO DIN – MASCHIO GAS CILINDRICO  
ORIENTABILE  
45° RENVERSÉ ORIENTABLE AVEC CONTRÈ ÈCROU DIN/BSPP  
EINSTELLBARE 45°-VERSCHRAUBUNG MIT KONTERMUTTER –  
DIN 24° / AGR-Z REDUZIERT  
RACOR 45° ORIENTABLE CON CONTRATUERCA DIN/BSPP

F1 Metrisch, Metrico, Metric, Métrique, Métrico

F2 Zylinder-Gasgewinde, Gas cilindrico, BSPP, Gaz cylindrique,  
Gas cilíndrica

Code	Thread		Dimensions						Pressure		Series
	F1	F2	T1	H	L1	L2	L3	L4	Bar	Psi	
			mm	mm	mm	mm	mm	mm			
QME06LMOG02.1	12X1,5	1/8"	6	14	6,3	9,5	21,7	13,3	315	4568	L
QME08LMOG04.1	14X1,5	1/4"	8	14	9,5	12	19,5	16,5	315	4568	L
QME10LMOG04.1	16X1,5	1/4"	10	14	9,5	12	24,5	16,5	315	4568	L
QME12LMOG06.1	18X1,5	3/8"	12	19	9,5	14	27,5	16,5	250	3626	L
QME15LMOG08.1	22X1,5	1/2"	15	22	13	17	26	20	250	3626	L
QME18LMOG08.1	26X1,5	1/2"	18	27	13	17	32	20,5	250	3626	L
QME22LMOG12.1	30X2	3/4"	22	27	13	19,5	37,5	20,5	160	2320	L
QME28LMOG16.1	36X2	1"	28	33	16	23	36	23,5	160	2320	L
QME35LMOG20.1	45X2	1.1/4"	35	41	16	27	38	26,5	160	2320	L
QME42LMOG24.1	52X2	1.1/2"	42	48	16	26	38	27	160	2320	L
QME06SMOG04.1	14X1,5	1/4"	6	14	9,5	11	18,5	16,5	315	4568	S
QME08SMOG04.1	16X1,5	1/4"	8	14	9,5	13	22,5	16,5	315	4568	S
QME10SMOG06.1	18X1,5	3/8"	10	19	9,5	13	24,5	17	250	3626	S
QME12SMOG06.1	20X1,5	3/8"	12	19	9,5	17	24,5	17	250	3626	S
QME14SMOG08.1	22X1,5	1/2"	14	22	13	16	25,5	21	250	3626	S
QME16SMOG08.1	24X1,5	1/2"	16	27	13	16	31	21,5	250	3626	S
QME20SMOG12.1	30X2	3/4"	20	27	13	19	33	23,5	250	3626	S
QME25SMOG16.1	36X2	1"	25	33	16	22	35	28	250	3626	S
QME30SMOG20.1	42X2	1.1/4"	30	41	16	24	37	29,5	160	2320	S
QME38SMOG24.1	52X2	1.1/2"	38	48	16	24	37	32	160	2320	S